



# Get the Lead Out: Take Advantage of Unit Turnover

Using unit turnover to make sure units are lead-safe is not difficult. Here are a few simple things you can do to make the most of this time:

## Inspect the unit.



- Inspect doors, window sills, stairways and painted floors for peeling or chipping paint. Be sure to check both interior and exterior painted surfaces.
- Make sure windows and doors move easily. Window friction can be a major source of fine lead dust.
- Check outside for bare soil, particularly close to the building, on walking paths, or places where children play. Lead from exterior paint and prior use of leaded gasoline can build up in soil. Lead from soil can be carried into the building on clothes and shoes.

## Carefully repair all damaged paint surfaces and hazardous areas.



- Cover the work area with durable protective sheeting (plastic or poly) to prevent the spread of lead and make cleanup easier.
- Mist painted surfaces with water before sanding and scraping to avoid creating dust.
- If you use power sanders or grinders, be sure they have an HEPA-filtered vacuum attachment.
- Do not use open flame or high heat to remove paint, as these methods are not safe for you or your tenants.
- It is best to cover painted floors with new flooring. Leaded paint can make lead dust even if the paint looks good.
- Consider replacing windows that are in poor condition. This can remove a major source of lead dust and save energy.
- Plant grass and small shrubs, use crushed stone, or spread mulch to cover bare soil.





## Identify and address any underlying problems.

- Fix moisture problems and water damage now. This will give your lead-safe work the best chance of lasting for years to come.



## Thoroughly clean the unit to remove any lead dust from repairs.

- Pick up large paint chips and visible dust with a wet paper towel.
- Mist protective sheeting with water before folding it up and putting it into a heavy duty trash bag.
- Using a HEPA vacuum, slowly vacuum surfaces, especially windowsills and floors, including corners and the areas between floorboards.
- Scrub windowsills and floors with soap and water. Be sure to use two buckets, one with clean soapy water, and the for rinse water. Once areas are cleaned with soap, repeat this process with clean water.
- Pour used cleaning and rinse water down the toilet.
- Put all trash from your work and cleanup into plastic trash bags. Seal all trash bags with tape before throwing them into a dumpster or in the trash.

## For more information about taking advantage of unit turnover to create lead-safe housing, please contact:

*Childhood Lead Poisoning Prevention Unit  
Maine Center for Disease  
Control and Prevention*

Phone toll free in Maine: 866-292-3474

Phone: 207-287-4311

TTY: Call Maine Relay 711

*Lead Hazard Prevention Program  
Maine Department of Environmental Protection*

Phone toll free: 800-452-1942

Phone: 207-287-7751

TTY: 800-492-0859

Also see *Lead Paint Safety Guide for Painting, Home Maintenance and Renovation Work*.

This guide can be found online at <http://www.maine.gov/healthyhomes>. You can also request a copy from the Environmental Protection Agency (EPA) by calling 1-800-424-LEAD.

The Department of Health and Human Services (DHHS) does not discriminate on the basis of disability, race, color, creed, gender, age, sexual orientation, or national origin, in admission to, access to or operation of its programs, services, activities or its hiring or employment practices. This notice is provided as required by Title II of the Americans with Disabilities Act of 1990 and in accordance with the Civil Rights Acts of 1964 as amended, Section 504 of the Rehabilitation Act of 1973 as amended, the Age Discrimination Act of 1975, Title IX of the Education Amendments of 1972 and the Maine Human Rights Act. Questions, concerns, complaints, or requests for additional information regarding civil rights may be forwarded to the DHHS' ADA Compliance/EEO Coordinator, State House Station #11, Augusta, Maine 04333, 207-287-4289 (V) or 207-287 3488 (V), TTY: Call Maine Relay 711. Individuals who need auxiliary aids for effective communication in programs and services of DHHS are invited to make their needs and preferences known to the ADA Compliance/EEO Coordinator. This notice is available in alternate formats, upon request.